

MFS Soft Shield

SOFT ARMOR SHIELDS



Inside Closed



Outside Open

- Foldable rapid deployment shield
- Fits two piece custom ballistic which provides overlap at center
- Webbing handle and webbing forearm channel/route for stabilization / easy of carry
- Dual 1" webbing on primary handle to allow LED wire to route between
- Button holes routing to allow wire concealment
- Removable handle cover to conceal LED battery pack
- Removable LED light fixture holster with laser cut-out and wire routing
- Webbing tabs on left and right sides
- Flap with molle to accommodate accessories, channel/routing beneath flap
- Internal bottom loading plate pocket which is suspended from top
- Hook/Loop ballistic opening
- Removable tab that attached to metal bracket to secure in vehicle
- Loop on strike face below LED fixture for removable identification panel
- Available Colors: Black and Ranger Green

Ballistics IIIA

Protecting your community starts with equipping yourself with body armor that not only meets the highest level of protection but also exceeds your expectations for lightweight comfort and performance. We currently have more NIJ .06 certified products than any other ballistics company in the industry with a key emphasis of providing our customers with lighter, more flexible body armor systems with greater ballistic capabilities.

Specifications

AXIIIA-1, BIIIA-2 and CIIIA-3 satisfies the requirements of NIJ-Standard-0101.06 Level IIIA and the Compliance Testing Program.

Model	Weight (.psf)	Thickness (inches)
CIIIA-3	1.42	0.34
BIIIA-2	0.96	0.25
AXIIIA-1**	0.87	0.20

** Exceeds new FBI 4.1 requirements.

Hard Armor Plates



Protection Type / Level: Special (Rifle)

Configuration: ICW

Thickness: .80" ± 0.125"

Curvature: Multi-Curve

Construction: Ceramic / Composite

HARD ARMOR PLATE - OMEGA PLUS

Rounds defeated:

- 5.56mm x 45mm (M855)
- 7.62mm x 39mm (PS Ball/MSD)
- 7.62mm x 51mm (M80)



AXIIIA
SOFT ARMOR
Weight = 0.87 psf
Thickness = 0.20"

EliteProven.com



*All weights are approximate